



DURABAND2



FUNCTIONALITY

| | |
|------------------------------|----------------------------------------|
| RF Protocol: | ISO 15693 |
| Operating Frequency: | HF - 13.56 MHz |
| Memory Configuration: | 16 Character UID, 896 bits User Memory |
| R/W Capability: | Read/Write |

PERFORMANCE

| | |
|---------------------------|-----------------|
| Read Range: | Less than 1" |
| Quality Guarantee: | 100% |
| Orientation: | Front Face Read |
| IP Rating: | IP68 |

PHYSICAL

| | |
|-------------------------|-------------------------------------|
| Material: | PC/PBT Alloy |
| Mounting System: | Metal Band (Pass-through Slot 5/8") |
| Color: | Custom Logo Available |

OPERATIONAL

| | |
|--------------------------------------------|--------------|
| Max Temperature Exposure: | 260°F/ 125°C |
| Min Temperature Exposure: | -40°F/ -40°C |
| Continuous Max Service Temperature: | 260°F/ 125°C |
| Continuous Min Service Temperature: | -40°F/ -40°C |
| IK Impact Rating: | IK10 |
| Water and Ice Proof: | Yes |

DIMENSIONS

| | |
|--------------------|-------------|
| Weight: | 5g / .17 oz |
| Dimensions: | 1.5" x .75" |
| Thickness: | .38" |



RECOMMENDED TAG APPLICATIONS

Hose: Industrial & Chemical Hose, Pipes

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email sales@infochip.com or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

Where is it?

What is it?

Is it safe to use?

(877) 747-2447

sales@infochip.com

www.infochip.com