



DURABAND2



FUNCTIONALITY

RF Protocol:	EPC Class 1 Gen 2: ISO 18000-6C
Operating Frequency:	UHF - (NA): 902 to 928 MHz (EU): 866 to 868 MHz
Memory Configuration:	96-Bit EPC; 512-Bit User Memory; 64-Bit TID
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	10ft (results may vary)
Quality Guarantee:	100%
Orientation:	Readable in 360° - Range varies with orientation
IP Rating:	IP68

PHYSICAL

Material:	PC/ PBT Alloy
Mounting System:	Metal Band (Pass-through Slot 5/8")
Color:	Custom logo available

OPERATIONAL

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	4.9g / .17 oz
Dimensions:	1.5" x .75"
Thickness:	.25"



RECOMMENDED TAG APPLICATIONS

Hose: Industrial & Chemical Hose, Pipes

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email sales@infochip.com or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

Where is it?

What is it?

Is it safe to use?

(877) 747-2447

sales@infochip.com

www.infochip.com