



DURADROP



FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Up to 0.1"
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

PHYSICAL

Material:	Stainless Steel
Mounting System:	Hook, Tie, Rope
Color:	Custom Logo Available (laser etching on back of product only)

OPERATIONAL

Continuous Max Service Temperature:	257°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

PRODUCT

Weight:	17g/ 0.59oz
Dimensions:	28.0 mm x 35.0 mm
Thickness:	3.65 mm



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Valves, Pipes & Industrial Equipment
Tools & Machinery

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email sales@infochip.com or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

Where is it?

What is it?

Is it safe to use?

(877) 747-2447

sales@infochip.com

www.infochip.com