



# DURAFOB



## FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

## PERFORMANCE

Read Range:	Less than 1"
Quality Guarantee:	100%
Orientation:	Two Face Read
IP Rating:	IP68

## PHYSICAL

Material:	Plastic
Mounting System:	Key Ring
Color:	Yellow, Black, Orange, Blue

## OPERATIONAL

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

## DIMENSIONS

Weight:	4g / .14 oz
Dimensions:	1.5" x 1.25"
Thickness:	.13"



## RECOMMENDED TAG APPLICATIONS

Safety:	Fall Protection
Access Control:	Security Fob

Visit [www.infochip.com](http://www.infochip.com) to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email [sales@infochip.com](mailto:sales@infochip.com) or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

**Where is it?**

**What is it?**

**Is it safe to use?**

(877) 747-2447

[sales@infochip.com](mailto:sales@infochip.com)

[www.infochip.com](http://www.infochip.com)