



# DURAPLUG6 PPA

(For high temp or pressure see DuraPlug6 PEEK)



## FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

## PERFORMANCE

Read Range:	Up to 0.1"
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

## PHYSICAL

Material:	PPA + GF30%
Mounting System:	Metal-embeddable, Press Fit
Color:	Custom Logo and Colors Available

## OPERATIONAL

Max Temperature Exposure:	212°F/ 100°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	212°F/ 100°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

## DIMENSIONS

Weight:	.17g/ .01 oz
Dimensions:	Diameter 0.236" (6mm)
Thickness:	.089" (2.25mm)



## RECOMMENDED TAG APPLICATIONS

**Lifting:** Shackles, Chain Slings & Other Industrial Equipment

Visit [www.infochip.com](http://www.infochip.com) to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email [sales@infochip.com](mailto:sales@infochip.com) or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

**Where is it?**

**What is it?**

**Is it safe to use?**

(877) 747-2447

[sales@infochip.com](mailto:sales@infochip.com)

[www.infochip.com](http://www.infochip.com)