



# DURATRAK



## FUNCTIONALITY

<b>RF Protocol:</b>	EPC Class 1 Gen 2: ISO 18000-6C
<b>Operating Frequency:</b>	UHF - (NA): 865 to 956 MHz (EU): 865 to 956 MHz
<b>Memory Configuration:</b>	96 Bit Serialized TID; 128-EPC Bit Memory
<b>R/W Capability:</b>	Read/Write

## PERFORMANCE

<b>Read Range:</b>	Up to 26.2 feet
<b>Quality Guarantee:</b>	100% & 2 years
<b>Orientation:</b>	Linear
<b>IP Rating:</b>	IP68

## PHYSICAL

<b>Material:</b>	PC/ABS high impact
<b>Mounting System:</b>	Screw
<b>Color:</b>	Pantone blue 287C or grey

## OPERATIONAL

<b>Max Temperature Exposure:</b>	185°F/ 85°C
<b>Min Temperature Exposure:</b>	-40°F/ -40°C
<b>Continuous Max Service Temperature:</b>	185°F/ 85°C
<b>Continuous Min Service Temperature:</b>	-40°F/ -40°C
<b>Water and Ice Proof:</b>	Yes

## DIMENSIONS

<b>Weight:</b>	0.5 oz/ 16 g
<b>Dimensions:</b>	3.6" x 1.1"
Width	0.6



## RECOMMENDED TAG APPLICATIONS

**Oil & Gas:** Industrial Equipment, Tools & Machinery

Visit [www.infochip.com](http://www.infochip.com) to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email [sales@infochip.com](mailto:sales@infochip.com) or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

**Where is it?**

**What is it?**

**Is it safe to use?**

(877) 747-2447

[sales@infochip.com](mailto:sales@infochip.com)

[www.infochip.com](http://www.infochip.com)