

PIPETRACKER



FUNCTIONALITY

RF Protocol: EPC Class 1 Gen 2; ISO 18000-6C
Operating Frequency: UHF - 860 to 960 MHz

Memory Configuration: 96 EPC Bits; 512 Bit User Memory
R/W Capability: Read/Write

PERFORMANCE

Read Range: Up to 3ft (results may vary)

Quality Guarantee: 100%

Orientation: Readable in 360° - Range varies with orientation

IP Rating: IP68

PHYSICAL

Material: Steel

Mounting System: Metal Pipe Cinch

Color: Steel

OPERATIONAL

Max Temperature Exposure: 300°F/ 150°C

Min Temperature Exposure: -40°F/ -40°C

Continuous Max Service Temperature: 300°F/ 150°C

Continuous Min Service Temperature: -40°F/ -40°C

Water and Ice Proof: Yes

DIMENSIONS

Weight:	48g / 1.69 oz
Dimensions:	1.25" x 1"
Thickness:	.41"



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Surface Pipe

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email sales@infochip.com or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

Where is it?

What is it?

Is it safe to use?