



SYNTHETIC TAG



FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Less Than 1"
Quality Guarantee:	100%
Orientation:	Two Face Read
IP Rating:	IP68

PHYSICAL

Material:	Plastic
Mounting System:	String/Thread
Color:	Cream (Off White)

OPERATIONAL

Max Temperature Exposure:	320°F/ 160°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	320°F/ 160°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	1g / .04 oz
Dimensions:	Diameter .6"
Thickness:	.11"



RECOMMENDED TAG APPLICATIONS

Lifting: Synthetic Slings & Harnesses

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email sales@infochip.com or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

Where is it?

What is it?

Is it safe to use?

(877) 747-2447

sales@infochip.com

www.infochip.com