



DATABANDMICRO+



FUNCTIONALITY

| | |
|------------------------------|--|
| RF Protocol: | ISO 15693 |
| Operating Frequency: | HF - 13.56 MHz |
| Memory Configuration: | 16 Character UID, 896 bits User Memory |
| R/W Capability: | Read/Write |

PERFORMANCE

| | |
|---------------------------|-----------------|
| Read Range: | Up to .5" |
| Quality Guarantee: | 100% |
| Orientation: | Front Face Read |
| IP Rating: | IP68 |

PHYSICAL

| | |
|-------------------------|--|
| Material: | PC/PBT Alloy |
| Mounting System: | Metal Band 0.25" wide max. Cable Tie 0.25" x 0.055" max; 0.10" Dia Wire Rope max |
| Color: | Custom Logo and Colors Available |

OPERATIONAL

| | |
|--|--------------|
| Max Temperature Exposure: | 260°F/ 125°C |
| Min Temperature Exposure: | -40°F/ -40°C |
| Continuous Max Service Temperature: | 260°F/ 125°C |
| Continuous Min Service Temperature: | -40°F/ -40°C |
| Water and Ice Proof: | Yes |

DIMENSIONS

| | |
|--------------------|---------------|
| Weight: | 1.4g / .05 oz |
| Dimensions: | 0.88" x .5" |
| Thickness: | .25" |



RECOMMENDED TAG APPLICATIONS

Hose: Hydraulic Hose, Chemical Hose & Pipe

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more!
For pricing and details, please call 1-816-421-2553.

Holland RFID
(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>