

# Features

- ◀▶ 1 ... 3 cm Reading distance
- 📄 4 rows OLED-Display
- 🔊 Tone and Vibration Feedback
- 📄 1000 UIDs read
- 📶 2000 Bluetooth read
- 🖥️🤖 Apps with Remote Read button
- 📶🔌 Bluetooth, USB, HID Interface
- 🕒 Real-Time Clock
- 🛡️ ATEX certified version
- 🌡️ Temperature : 0°C ... + 60°C
- 🛡️ IP 54 certified
- 🇪🇺 APOLLO-MP-LF / HF
- 🇩🇪 Made in Germany

The HID (Human Interface Device) keyboard wedge function sets the UID after reading directly at the place of cursor position in **Microsoft Word™**, **Excel™** or similar software tools on **Android™**.



[www.tec-tus.de](http://www.tec-tus.de)  
[info@tec-tus.de](mailto:info@tec-tus.de)

© TECTUS reserves the right to change any information or data in this document and product without prior notice to third parties.

Android™ is a reg. trademark of Google™ Corp.  
Microsoft Word™ and Excel™ are reg. trademarks of Microsoft Corp.



# MultiPen

## An innovative RFID + NFC Mobile Reader

LF 125kHz  
LF 134,2 kHz FDX-B + HDX  
HF and NFC 13,56 MHz  
UHF 868 MHz

[www.tec-tus.de](http://www.tec-tus.de)  
[info@tec-tus.de](mailto:info@tec-tus.de)

TECTUS Transponder Technology GmbH  
Eurotec-Ring 39 \_ D-47445 Moers \_ Germany

**3 in 1\***

## Reads UIDs of passive RFID tags with different Frequency range combinations.



+



LF	HF	UHF
125 134.2	& 13.56	& 868
kHz	MHz	MHz

\*All configurations possible

The MultiPen makes RFID/NFC applications in mobile maintenance, inventory /asset management, guards control systems and logistics easy and efficient.

If RFID/NFC TAGs are mounted very close to each other or placed in the corner the small reading tip makes it possible to read the tags, so every equipment can be easily identified.



Weight : 125 g

L : 190 mm

W : 30 mm

D : 35 mm

Picture 1:1

